

产品介绍 Overview

- PVC 纤维增强管是工业、农业、渔业、建筑及家居等普通设备供水、气、油的理想管材，具有透明、无毒、无味、耐压、抗拉伸、耐腐蚀、耐老化，外型美观、柔软轻便的特点。

产品细节 Details



产品尺寸 Dimensions

内 径		壁 厚		工作压力 (MPa)	试验压力 (MPa)	爆破压力 (MPa)	近似米重 (g/m)
公称内径 (mm)	极限偏差 (mm)	公称壁厚 (mm)	极限偏差 (mm)				
φ 5	0.3	1.75	0.2	0.6	0.8	1.0	50
φ 5	0.3	2.5	0.3	1.0	1.3	1.6	80
φ 6	0.3	2.0	0.3	0.8	1.0	1.4	70
φ 6	0.2	3.0	0.3	1.0	1.2	1.6	115
φ 8	0.3	1.7	0.3	0.3	0.5	0.8	70
φ 8	0.3	2.0	0.3	0.5	0.8	1.0	85
φ 8	0.3	2.4	0.4	0.8	1.0	1.4	107
φ 8	0.3	2.75	0.4	1.0	1.2	1.6	127
φ 8	0.3	3.0	0.4	1.4	1.6	2.0	142
φ 8.5	0.3	2.5	0.4	0.8	1.0	1.4	118
φ 9	0.3	2.0	0.4	0.5	0.7	0.9	95
φ 9	0.3	2.5	0.4	0.6	0.8	1.0	123
φ 9	0.3	3.0	0.4	0.7	0.9	1.2	154
φ 10	0.3	2.0	0.5	0.5	0.7	0.9	103
φ 10	0.3	2.5	0.5	0.7	0.9	1.2	134
φ 10	0.3	3.0	0.5	1.0	1.2	1.5	167
φ 12	0.3	2.5	0.5	0.5	0.7	0.9	155
φ 12	0.4	3.0	0.5	0.8	1.0	1.4	192
φ 13	0.4	2.5	0.5	0.5	0.7	0.9	165
φ 14	0.4	2.5	0.5	0.5	0.7	0.9	176
φ 14	0.4	3.0	0.5	0.7	0.9	1.2	218
φ 15	0.4	2.5	0.5	0.5	0.7	0.9	187
φ 16	0.4	2.2	0.5	0.3	0.4	0.6	171
φ 16	0.4	2.5	0.5	0.4	0.5	0.7	198
φ 16	0.4	2.75	0.5	0.6	0.8	1.0	220
φ 16	0.4	3.0	0.5	0.7	0.7	1.2	245
φ 17	0.4	2.75	0.5	0.5	0.7	0.9	232
φ 18	0.5	2.5	0.5	0.4	0.6	0.8	220
φ 18	0.5	3.0	0.5	0.5	0.7	0.9	270
φ 19	0.5	3.0	0.5	0.5	0.7	0.9	280
φ 20	0.5	2.5	0.5	0.3	0.4	0.6	240
φ 20	0.5	3.0	0.5	0.4	0.6	0.8	295
φ 20	0.5	3.5	0.5	0.6	0.8	1.0	350
φ 22	0.5	3.0	0.5	0.5	0.7	0.9	320
φ 22	0.5	3.5	0.5	0.6	0.8	1.0	380
φ 24.5	0.6	3.0	0.5	0.4	0.6	0.8	352
φ 25	0.6	2.5	0.5	0.3	0.4	0.6	295
φ 25	0.6	2.75	0.5	0.3	0.4	0.6	325
φ 25	0.6	3.0	0.5	0.4	0.6	0.8	358
φ 25	0.6	4.0	0.6	0.5	0.8	1.0	495
φ 28.5	0.6	3.0	0.6	0.3	0.4	0.6	402
φ 30	0.8	3.5	0.8	0.3	0.4	0.6	500
φ 32	0.8	4.0	0.8	0.3	0.4	0.6	615
φ 32	1.0	5.0	1.0	0.4	0.5	0.7	787
φ 38	1.0	4.5	1.0	0.3	0.4	0.5	815
φ 42	1.0	4.2	1.0	0.3	0.4	0.5	825
φ 48	1.2	5.0	1.5	0.2	0.3	0.4	1130
φ 50	1.2	5.0	1.5	0.2	0.3	0.4	1170

产品广泛应用于石油、化工、钢铁、制药、环保、矿山、造纸、城建、给排水等行业



造纸行业



环保行业




化工行业



排水行业



矿山行业



钢铁行业