



产品介绍

安全型压线帽


- ◆外壳材质: UL 认可之尼龙66, 防火等级94V-2。
- ◆使用方法: 将电线尾部外皮剥去再插入套管内, 用压线钳压紧即可。
- ◆特点: 外壳为尼龙注塑成型、内部铜管特长, 增加电线压接范围使其更易于导电, 并能夹住电线, 即使强烈振动亦不脱落。



Underwriters
Laboratories Inc.
File E 312853

Safety-type Wire Joints

- ◆Shell material: Nylon 66, 94V-2, certificated agree, by UL.
- ◆Usage: Peel the coat of wire, then insert to tube, use pincers to fix them.
- ◆Feature: Nylon shell, long copper tube, easy to conduct electricity and hold wire tightly.



(CHS- ϕ 3- ϕ 10)



◎技术参数

编号 Item NO.	A(高) (mm)	W(宽)		铜管内径 D (mm)	适用电线范围 mm ²	Suitable Wires Awg
		B (mm)	C(mm)			
UL CHS- ϕ 3	18	9	3.6	2.8	1.25	22-16
UL CHS- ϕ 4	21	9.5	3.9	3	2	16-14
CHS- ϕ 5	22.5	10.5	4.8	4	5.5	12-10
CHS- ϕ 6	24	12	5.6	4.8	8	8
CHS- ϕ 7	25.5	13	6.5	5.5	10	8-6
CHS- ϕ 8	25.5	14	7.5	6	13	6
CHS- ϕ 10	29.5	15.5	9.3	7.8	16	4

◎ 产品细节



◎ 品牌授权

